



**The world's first
field mountable
videographic recorder
LINAX A305**

LINAX A305



LINAX A305 ►

LINAX A3xx ▼



Main features

- Panel depth only 50 mm
- Universal mounting: Panel/Wall/Pipe
- High performance
 - 100 ms sampling rate per channel
 - 500 V isolation channel to channel
 - 6 digit digital indicators
- Online help function
- Modbus master function

LINAX at a glance



Features	LINAX A305	LINAX A310	LINAX A320	LINAX A330
Display	14.4 cm (5.7 in.) TFT 12 cm (4.7 in.) monochrome FSTN	12.5 cm (5 in.) LCD	14.4 cm (5.7 in.) TFT	31 cm (12.1 in.) TFT
Operating keys	6 keys	6 keys	Touchscreen	8 keys
Front panel and depth in mm	144 x 144 x 50	144 x 144 x 195	144 x 144 x 195	288 x 288 x 195
Channels	8 (4 analog inputs)	12	12	36
Internal memory	8 MB	1 MB	8 MB	8 MB
RS 485 Communication	Not available	Optional: Modbus RTU	Optional: Modbus RTU	Optional: Modbus RTU
Ethernet Communication	Optional: TCP/IP, HTTP, SMTP, FTP (Server), Modbus TCP (Slave/Master) Webserver, email	Optional: TCP/IP, email, FTP (Server), HTTP	Optional: TCP/IP, email, FTP (Server), HTTP	Standard: TCP/IP, email, FTP (Server), HTTP
Power supply for 2-wire instruments	2 loops optional	12 loops optional	2 loops standard 12 loops optional	2 loops standard 12 loops optional
Totaliser	16 optional	12 optional	12 standard	72 standard
Process alarms	32	24	24	144
Process groups	2	2	2	6
Mathematic and logic functions	optional	Not available	optional	optional
FDA 21 CFR PART 11	standard	standard	standard	standard
IP66 / NEMA4x	standard	standard	standard	standard

Customer benefits

- Guaranteed data integrity
- Unsurpassed device protection (Flash memory, NEMA4X)
- Low total cost of ownership
- Easy system integration
- Easy to use
- Universal mounting (A305)



Rely on us.

Camille Bauer AG
Aargauerstrasse 7
CH-5610 Wohlen / Switzerland
Phone: +41 56 618 21 11
Fax: +41 56 618 35 35
e-Mail: info@camillebauer.com
www.camillebauer.com